

PRODUCT SELECTION GUIDE

Symbol Legend

- Suited
- Well Suited
- Preferred
- ✗ Not Recommended



CIM 500



CIM 800



CIM 1000

Below grade waterproofing	●	●●	●●●
Negative side waterproofing	●	●●	●●●
UV Exposed	✗	●	●●●
Between slab waterproofing	●	●●	●●●
Under tile/stone waterproofing	●	●●	●●●
Immersion/ponding conditions	✗	✗	●●●
Planter box waterproofing	●	●●	●●●
Fish ponds, zoo & aquariums*	✗	✗	●●
Potable water & reservoirs*	CIM 1061 For use where ANSI/NSF approval is required		

SUPPORTING PRODUCTS

CIM 500V For use on vertical waterproofing and detailing of CIM 500 applications

CIM 1061* Use on applications where ANSI/NSF approval is required such as potable water and wildlife contact

CIM 1000TG Use for waterproofing detail work such as construction joints and crack repair

CIM EMT Primer Use on damp porous surfaces to improve adhesion.

CIM Bonding Agent Use on non-porous surfaces to maximize adhesion. Use on CIM outside of recoat window as directed when multiple coats are required.

WARRANTY INFORMATION

CIM 500 5 and 10 year warranties in approved applications based on application thickness

CIM 1000 Up to 20 year warranty based on application thickness

CIM 1000 and CIM 1061 5 or 10 year immersion warranty based on application thickness

Published data and specifications subject to change without notice

Contact us for information



www.ChaseCorp.com/CIMIndustries/Cim-500

[Twitter](#) [YouTube](#) [LinkedIn](#) /CIM Ind

